



SX50-A

Base Model Pit Bike
50.53 cc | 2 Stroke
48.5 lbs. | 49" x 23" x 31"

ENGINE	
Bore And Stroke	44.02mm x 33.2mm
Carburetor	16mm
Max Output	2.4 hp @ 7000 rpm
Ignition	Coil
Start Mode	Pull Start
Transmission	Automatic
CHASSIS	
Front Suspension	Spring, Inverted
Rear Suspension	190.5mm Shock
Brake	Disc Disc
Tire	2.50-10 2.50-10
Frame	Steel
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	36 inches
Seat Height	23 inches
Ground Clearance	8.5 inches



SR70C

Base Model Pit Bike
72 cc | 4 Stroke
113 lbs. | 53" x 24" x 31"

ENGINE	
Bore And Stroke	47mm x 41.4mm
Carburetor	16mm
Max Output	4.69 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Down Semi-Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265mm Shock
Brake	Disc Disc
Tire	2.50-10 2.50-10
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	43 inches
Seat Height	22.5 inches
Ground Clearance	6 inches



SR70AUTO

Base Model Pit Bike
72 cc | 4 Stroke
113 lbs. | 53" x 24" x 31"

ENGINE	
Bore And Stroke	47mm x 41.4mm
Carburetor	16mm
Max Output	4.69 hp @ 7500 rpm
Ignition	CDI
Start Mode	Electric Start
Transmission	Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	255mm Shock
Brake	Disc Drum
Tire	2.50-10 2.50-10
Frame	Double Bar Steel Frame
Swingarm	Steel, "A" Type
DIMENSIONS	
Wheelbase	39 inches
Seat Height	21.5 inches
Ground Clearance	5 inches



SR110SEMI

Base Model Pit Bike
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"

ENGINE	
Bore And Stroke	52.4mm x 49.5mm
Carburetor	16mm
Max Output	6.2 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Semi-Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265mm Shock
Brake	Disc Disc
Tire	2.75-12 3.00-10
Frame	Steel Back Bone
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	28 inches
Ground Clearance	10 inches



SR110DX

Deluxe Model Pit Bike
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"

ENGINE	
Bore And Stroke	52.4mm x 49.5mm
Carburetor	16mm
Max Output	6.2 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265mm Shock
Brake	Disc Disc
Tire	2.75-12 3.00-10 (Anodized Alloy Rims)
Frame	Steel Back Bone
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	29 inches
Ground Clearance	10 inches



SR125

Base Model Pit Bike
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm
Max Output	7.3 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275mm Shock
Brake	Disc Disc
Tire	2.50-14 3.00-12
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches



SR125SEMI

Base Model Pit Bike
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm
Max Output	7.3 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Semi-Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275mm Shock
Brake	Disc Disc
Tire	2.50-14 3.00-12
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches



SR125AUTO

Base Model Pit Bike
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm
Max Output	7.3 hp @ 7500 rpm
Ignition	CDI
Start Mode	Electric Start
Transmission	Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275mm Shock
Brake	Disc Disc
Tire	2.50-14 3.00-12
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches



SR125TR

TR Series Pit Bike
124 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm, Mikuni
Max Output	8.5 hp
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	Hydraulic, Inverted (Black)
Rear Suspension	290mm Shock, 850 lbs.
Brake	Disc Disc
Tire	60/100-14 80/100-12
Frame	Double Bar Steel Frame w/ Sub-Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches



SR140TR

TR Series Pit Bike
140 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"

ENGINE	
Bore And Stroke	55mm x 59mm
Carburetor	26mm, Mikuni
Max Output	12 hp
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	290mm Adjustable Shock, 1000 lbs.
Brake	Disc Disc
Tire	60/100-14 80/100-12
Frame	Double Bar Steel Frame w/ Sub-Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches



SR170TR

TR Series Pit Bike
169 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"

ENGINE	
Bore And Stroke	62mm x 56mm
Carburetor	26mm, Mikuni
Max Output	15.8 hp @ 9000 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	290mm Adjustable Shock, 1000 lbs.
Brake	Disc Disc
Tire	60/100-14 80/100-12
Frame	Double Bar Steel Frame w/Sub-Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches



SR170TX

TX Series Pit Bike
169 cc | 4 Stroke
149 lbs. | 68" x 29.5" x 42"

ENGINE	
Bore And Stroke	62mm x 56mm
Carburetor	26mm, Mikuni
Max Output	15.8 hp @ 9000 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	275mm DNM R/C Adjustable Shock
Brake	Disc Disc
Tire	60/100-14 80/100-12 (Kenda Tires)
Frame	Chromoly Steel Frame w/ Sub-Frame
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	30.5 inches
Ground Clearance	10.5 inches



SR150

Mid-size Dirt Bike
150 cc | 4 Stroke
227 lbs. | 73.2" x 31" x 44"

ENGINE	
Bore And Stroke	62mm x 49.6mm
Carburetor	28mm
Max Output	13.4 hp @ 9000 rpm
Ignition	CDI
Start Mode	Electric / Kick Start
Transmission	5 Speed Manual, 1-Down, 4-Up
CHASSIS	
Front Suspension	Hydraulic, Inverted, 230mm Trvl.
Rear Suspension	450mm Adj. Shock, 180mm Trvl.
Brake	Disc Disc
Tire	70/100-17 90/100-14
Frame	Cast Steel w/ Formed Steel Tube
Swingarm	Steel - Box Section
DIMENSIONS	
Wheelbase	51.5 inches
Seat Height	33.5 inches
Ground Clearance	11 inches



SR250S

Full-size Dirt Bike
249.6 cc | 4 Stroke
260 lbs. | 87" x 32.5" x 49"

ENGINE	
Bore And Stroke	77mm x 53.6mm
Carburetor	34mm
Max Output	25.8 hp @ 9000 rpm
Ignition	CDI
Start Mode	Electric / Kick Start
Transmission	5 Speed Manual, 1-Down, 4-Up
CHASSIS	
Front Suspension	R/C Adjustable, Inverted, 315mm Trvl.
Rear Suspension	P/R Adjustable Shock, 270mm Trvl.
Brake	Disc Disc
Tire	80/100-21 100/90-18
Frame	Aluminum Alloy
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	60 inches
Seat Height	37 inches
Ground Clearance	12 inches



SR450S

Full-size Dirt Bike
449 cc | 4 Stroke
265 lbs. | 91" x 32.7" x 51"

ENGINE	
Bore And Stroke	96mm x 62.1mm
Carburetor	36mm
Max Output	43.5 hp @ 7500 rpm
Ignition	CDI
Start Mode	Electric / Kick Start
Transmission	5 Speed Manual, 1-Down, 4-Up
CHASSIS	
Front Suspension	R/C Adjustable, Inverted, 315mm Trvl.
Rear Suspension	P/R Adjustable Shock, 270mm Trvl.
Brake	Disc Disc
Tire	80/100-21 110/100-18 (CST)
Frame	Aluminum Alloy
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	59 inches
Seat Height	37.8 inches
Ground Clearance	13 inches